

PIRA T motion detector

Switches on, switches off

Simple and effective



SENSNORM
certified




Recessed ceiling installation (DE):

Type	Application	Item no.
PIRA T8 DE	1-channel motion detector	1030200
PIRA T8-2 DE	2-channel motion detector - ideal for optimizing room ventilation	1030201
PIRA TC DE	Specially developed for corridors (rectangular detection area)	1030204
PIRA T6 Mini	Discreet mini sensor for unobtrusive installations	1030202

Surface-mounted (AP):

Type	Application	Item no.
PIRA T8 AP	1-channel motion detector	1030203
PIRA TC AP	Specially developed for corridors (rectangular detection area)	1030205
PIRA T0 AP	Outdoor detector for wall mounting (IP 55)	1030206



Functional description

- **Quick installation:** Thanks to plug-in terminals installed at a 45° angle, wiring is a breeze - even with 2 x 2.5 mm² Conductors
- **Simple operation:** via potentiometer
- **Optimized for LEDs:** LED switching load and zero-crossing circuit (tested with 40,000 switching cycles according to Theben standards)
- **Permanent light measurement:** The light is switched off when there is enough daylight - even when there is movement in the detection area.
- **SENSNORM and Theben standard tested:** Precise motion detection, even at higher room temperatures.
- **Uniform design:** For a harmonious overall appearance in any environment.

PIRA T motion detector Always the right choice Everything at a glance



PIRA T8 DE (article no. 1030200)

PIRA T8-2 DE (Article no. 1030201)

PIRA T8 AP (article no. 1030203)

- Switch-on brightness 5-1000 lx
- Switch-off delay 5 s-15 min
- Protection class IP 21
- Mounting height 2-3 m

Mounting height	Diagonally (t)	Head on to (r)
2,0 m	Ø 7 m	Ø 4 m
2,5 m	Ø 8 m	Ø 4 m
3,0 m	Ø 9 m	Ø 4 m

PIRA T6 Mini EN (article no. 1030202)

- Switch-on brightness 5-1000 lx
- Switch-off delay 5 s-15 min
- Protection class IP 21
- Mounting height 2-3 m



Mounting height	Diagonally (t)	Head on to (r)
2,0 m	Ø 6 m	Ø 3 m
2,5 m	Ø 6 m	Ø 3 m
3,0 m	Ø 7 m	Ø 4 m

PIRA TC DE (article no. 1030204)

PIRA TC AP (article no. 1030205)

- Switch-on brightness 5-1000 lx
- Switch-off delay 5 s-15 min
- Protection class IP 21
- Mounting height 2-3.5 m

Mounting height	Diagonally (t)	Head on to (r)
2,0 m	20 x 3 m	9 x 3 m
2,5 m	25 x 3 m	12 x 3 m
3,0 m	26 x 3 m	12 x 3 m



sens))) NORM certified


To rule out measurement errors and obtain reliable data, each measurement is repeated three times. The standardized measurements are carried out in accordance with the sens-NORM specifications.

More on this at
www.theben.de/pira-t

PIRA TO AP (article no. 1030206)

- Switch-on brightness 5-1000 lx
- Switch-off delay 5 s-15 min
- Protection class IP 55
- Mounting height 1.8-2.5 m
- Creep protection
- Exit-on function

Mounting height	Diagonally (t)	Head on to (r)
1,8 m	9 m	2 m
2,0 m	10 m	3 m
2,5 m	12 m	4 m



LUXA 103 presence detector

Now also available in a KNX version for ceiling installation



theben

Theben LUXA 103 presence detectors are the versatile device family for efficient lighting and HVAC control in indoor and outdoor areas. The devices with a round detection area are ideal for use in individual and open-plan offices, meeting rooms, storage rooms and basements as well as toilets. LUXA 103 corridor detectors with a rectangular detection area control the lighting in corridors, hallways and corridors. Thanks to color variants in white, grey and black, the surface-mounted devices blend harmoniously into any interior or exterior design.



Ceiling installation or flush mounting



Surface mounting with grey surface-mounted accessories




Surface mounting with black surface-mounted accessories

The highlights of the entire product family at a glance

- Elegant, timeless, flat design
- Convenient setting via app and remote control, only remote control or potentiometers
- Simple installation and wiring, for surface-mounted, recessed ceiling or flush-mounted installation
- Corridor detector in matching design language
- Device variant with second channel for HVAC control
- Integrated pushbutton input
- Protection class IP 54 for outdoor areas and damp rooms
- Perfect for high LED switching loads (at 230 V)
- Can be networked with other LUXA 103 devices or theMura Slave (at 230 V)

Presence detector LUXA 103 S360 DE KNX



- Presence detector (PIR) for ceiling mounting indoors or outdoors
- For KNX bus system, 2 channels light and 2 channels presence for HVAC control
- 2 channels of light with 1 light measurement
- Automatic lighting control with constant light control or switching operation
- Dimmable lighting in switching mode with and without daylight influence
- Integrated temperature sensor
- Day / night switchover via telegram
- Stand-by functionality (orientation light)
- 3 logic channels (AND/OR/XOR)
- KNX Data-Secure
- Operation as fully or semi-automatic possible
- Manual override possible via external KNX push-buttons

- One directional brightness measurement (mixed light measurement)
- Simple adjustment of the brightness measurement
- Short-term presence
- Selectable control speed
- Teach-in function
- Scene functionality
- Locking functions
- Switch-on delay and run-on time presence adjustable
- Extension of the detection range through parallel connection
- Detection sensitivity adjustable for outdoor use
- Test operation to check function and detection range
- Setting via ETS software (full range of functions)
- Setting via remote control/APP or APP (BLE)

Mounting type	Transverse detection area	Channels	Color	Type	Item no.
Recessed ceilings	113 m ² (ø 12 m 360°)	2 x light 2 x presence	White	LUXA 103 S360-12 KNX DE WH	1039053
	140 m ² (28 x 5 m)	2 x light 2 x presence	White	LUXA 103 S360-28 KNX DE WH	1039073

Details of the other 230 V and KNX versions of the LUXA 103 product family can be found at www.theben.de/LUXA103