

Селективность защит, сеть 240 В 1P/2P

Вышестоящий аппарат: IC60N/H/L, кривые C, D
Нижестоящий аппарат: IC60N/H/L, кривые B, C, D



Вышестоящий аппарат		IC60N/H/L													
Кривая C		Кривая C													
In (A)		1	2	3	4	6	8	10	16	20	25	32	40	50	63
Нижестоящий аппарат															
Предельный ток селективности (A)															
IC60N/H/L	0,5	30	T	T	T	T	T	T	T	T	T	T	T	T	T
Кривая B	0,75		70	260	T	T	T	T	T	T	T	T	T	T	T
	1		20	40	50	120	250	540	2700	T	T	T	T	T	T
	2			32	40	100	210	420	730	1500	3000	6400	9000	10000	
	3				48	64	130	270	420	570	1200	2100	5000	7500	
	4					64	120	190	290	400	580	1100	2200	2200	
	6						80	130	190	290	400	700	1100	1100	
	8						10	130	190	290	290	550	900	900	
	10							130	190	290	290	520	800	850	
	16										250	320	400	500	
	20										250	320	400	500	
	25											320	400	500	
	32												400	500	
	40														
Предельный ток селективности (A)															
IC60N/H/L	0,5		T	T	T	T	T	T	T	T	T	T	T	T	T
Кривые C, D	0,75		260	T	T	T	T	T	T	T	T	T	T	T	T
	1			40	50	120	250	540	2700	T	T	T	T	T	T
	2				48	100	210	420	730	1500	3000	6400	9000	10000	
	3					48	64	130	270	420	570	1200	2100	5000	7500
	4							190	290	400	580	1100	2200	2200	
	6							190	290	400	580	700	1100	1100	
	8								200	290	550	900	900	900	
	10									250	520	800	850	850	
	16										380	480	500	500	
	20										380	480	500	500	
	25											480	500	500	
	32												500	500	
	40														

Вышестоящий аппарат		IC60N/H/L													
Кривая D		Кривая D													
In (A)		1	2	3	4	6	8	10	16	20	25	32	40	50	63
Нижестоящий аппарат															
Предельный ток селективности (A)															
IC60N/H/L	0,5	T	T	T	T	T	T	T	T	T	T	T	T	T	T
Кривые B, C, D	0,75		260	T	T	T	T	T	T	T	T	T	T	T	T
	1		40	90	150	240	1000	1900	T	T	T	T	T	T	T
	2			70	150	280	350	1100	2600	5600	10000	T	T	T	T
	3				120	250	520	1000	1600	3600	10000	T	T	T	T
	4					90	120	370	640	800	1400	2100	7100	10000	
	6						120	190	450	590	900	1300	2200	2800	
	8							190	240	450	750	1300	1700	2000	
	10								190	240	600	950	1500	1700	
	16										380	480	1100	1300	
	20										380	480	900	750	
	25											480	500	750	
	32												500	750	
	40														

T Полная селективность до величины предельной отключающей способности нижестоящего аппарата.

4000 Предельный ток селективности – 4 кА.

Селективность не обеспечивается.